

LK-7030

LK-7030 is a silicone glycol copolymer soluble in water, alcohol and hydroalcoholic systems. it is hydrolytically stable. It is clear to slight hazy faint amber colour viscous liquid.

FEATURES

- Makes very stable formulations.
- Compatible with wide range of cosmetic ingredients.
- Usage level is very low.
- Good foam builder
- Imparts soft silky feel to the hair
- Non-irritant to skin.
- Ensures smooth wet shaving foams

APPLICATIONS

- **LK-7030 because of low order of acute toxicity that acts as surface tension depressant, wetting agent, emulsifier and foam builder in a wide variety of cosmetic and personal care products , including hair sprays , shampoos , skin care lotions , perfumes and shaving soaps.**
- LK-7030 fluid gives a stable foam , Stability of water solutions containing upto 5 % LK-7030 fluids are excellent.. Acid or Alkaline extremes reduce stability.
- Resin plasticizer in styling products.
- Humectant, emollient in skin products.

Product Name	Specific Gravity	Viscosity @ 25 Deg C.	Refractive Index	Cloud point Deg.C.	Flash point Deg.C.	Appearance
LK-7030	1.04-1.06	300-900	1.450-1.460	68-69	Above 100	Clear to slight hazy with faint amber colour viscous liquid.

[†] Typical Values – Should not be considered as specifications.

PACKING

30 kg. And 200 kg drums.

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

STORAGE & HANDLING

LK-7030 when stored at or below 16 Deg.C. it will become hazy and solidify to a soft wax which reliquaries on warming. Repeated freeze thaw cycle have no effect on product performance. When stored at or below 25 deg.C. in original unopened container this product has a usable life of 24 months from the date of production.

The information provided to the customers in this data sheet is intended as a guideline and is provided in good faith. The Information is believed to be accurate. Changes may occur from system to system as methods of use and conditions are beyond our control, hence **users are requested to evaluate the recommendations before actual application to get desired performance.**

ELKAY CHEMICALS PVT. LTD. (ELKAY) Main Plant Office (MIDC, Bhosari) exclusively can provide you with a specific written warranty for a particular use. In the absence of this, ELKAY gives the sole **warranty that the product (or products) supplied will meet its sales specifications** (not provided on this sheet). ELKAY disclaims any other expressed or implied warranty. For current or required specifications, please contact your ELKAY distributor, representative or office.

ELKAY does not warrant the recommendations given within for their fitness for use, performance, efficacy or safety. Users are responsible for certification of use of their product and for complying with local legislation. Suggestions of use shall not be taken as inducements to infringe any patents or grant any license under a valid patent and are provided for illustrative purposes only.

Internal References DX30701